C. 2.

6

Copy
RM E52K17

FEB 17 1953

NACA

RESEARCH MEMORANDUM

PERFORMANCE OF DOUBLE-SHROUD EJECTOR CONFIGURATION

WITH PRIMARY PRESSURE RATIOS FROM 1.0 TO 10

By Donald P. Hollister and William K. Greathouse

Lewis Flight Propulsion Laboratory
Cleveland, Ohio

CLASSIFICATION CHANGED

To   UNCLASSIFIED

NACA Res abs
Y RV-122   effective
By authority of _____ Date _____ Nov 8 1957
ART 12-19-57

NATIONAL ADVISORY COMMITTEE
FOR AERONAUTICS

WASHINGTON

February 10, 1953

2765

NATIONAL ADVISORY COMMITTEE FOR AERONAUTICS

RESEARCH MEMORANDUM

PERFORMANCE OF DOUBLE-SHROUD EJECTOR CONFIGURATION WITH

PRIMARY PRESSURE RATIOS FROM 1.0 to 10

By Donald P. Hollister and William K. Greathouse

SUMMARY

A brief investigation was made to determine the performance characteristics of a double-shroud cooling-air ejector configuration. Two convergent primary nozzles were used to simulate a specific manufacturer's iris-type variable-area nozzle in the open and closed positions. The investigation comprised four phases: (1) obtaining performance with no secondary or tertiary air flow (cooling-air passages blocked), (2) determining the tendency for backflow to occur in either cooling-air passage, (3) determining the sensitivity of flow in one passage to that in the other, and (4) obtaining pumping and thrust characteristics with secondary and tertiary air flow.

The experimental results showed that the performance with the cooling-air passages blocked was typical of that for single ejectors having diameter and spacing ratios similar to those used in this investigation. There was a tendency for backflow to occur, but the magnitude of such flow was relatively small. The weight flow of each ejector was shown to be essentially independent of the other, and the closed primary-nozzle configuration was found to be generally capable of pumping more cooling-air than the open primary-nozzle configuration. Gains in gross thrust were observed for both configurations, with losses occurring only at low secondary and tertiary pressure ratios.

INTRODUCTION

The use of afterburners for thrust augmentation, and particularly the advent of high-temperature afterburners, increases the cooling-air requirements of turbojet engines. Single-shroud ejectors are now being used for supplying the cooling air. In some aircraft installations, however, it is necessary to provide an additional quantity of air for cooling the aircraft structure; the use of double-shroud ejectors for meeting this requirement is now under consideration.

The single-shroud ejector has been the subject of several experimental investigations (references 1 to 7), but the available information on double-shroud ejectors is very limited. In reference 8, the operating mechanism of double-shroud ejectors is discussed, the performance of several configurations is presented, and it is shown that an ejector of this type can be designed to operate satisfactorily.

The double-shroud ejector configurations used in this investigation incorporated two convergent primary nozzles to simulate a specific manufacturer's iris-type variable-area nozzle in the closed and open positions. Although this investigation was limited to only two configurations, a wider range of pressure ratios and operating conditions was covered than in the investigation reported in reference 8, which primarily presented the pumping and thrust characteristics of each configuration for only four primary pressure ratios. In the present investigation, the thrust and pumping characteristics of both configurations were investigated for eight constant primary pressure ratios from 1.10 to 9.5. Additional tests were conducted to determine (1) ejector performance with no cooling-air flow, (2) the tendency for backflow to occur from the primary jet into either the secondary or the tertiary system, and (3) whether or not the flow through each cooling-air system was independent of the flow through the other. This investigation was conducted using dry unheated air at a temperature of 80° F.

SYMBOLS AND NOMENCLATURE

The following symbols and nomenclature used in this report are defined in the accompanying schematic sketch of a double-shroud ejector. It should be noted that primary refers to the engine nozzle, secondary denotes the inner annulus, and tertiary denotes the outer annulus:

2765

D_p	exit diameter of primary nozzle, in.
D_s	exit diameter of inner shroud, in.
D_t	exit diameter of outer shroud, in.
D_s/D_p	inner-shroud diameter ratio
D_t/D_p	outer-shroud diameter ratio
F_{ej}	gross thrust of ejector, lb
F_j	gross thrust of primary nozzle with shrouds removed, lb
F_{ej}/F_j	gross thrust ratio

P_p primary-stream total pressure, in. mercury abs.

P_s secondary-stream total pressure, in. mercury abs.

P_t tertiary-stream total pressure, in. mercury abs.

P_p/P_0 primary pressure ratio

P_s/P_0 secondary pressure ratio

P_t/P_0 tertiary pressure ratio

P_a atmospheric pressure, in. mercury abs.

P_0 ambient exhaust pressure, in. mercury abs.

S_s distance from primary-nozzle exit to exit of inner shroud, inner-shroud spacing, in.

S_t distance from primary-nozzle exit to exit of outer shroud, outer-shroud spacing, in.

S_s/D_p inner-shroud spacing ratio

S_t/D_p outer-shroud spacing ratio

T_p primary-stream total temperature, $^\circ R$

T_s secondary-stream total temperature, $^\circ R$

T_t tertiary-stream total temperature, $^\circ R$

W_p primary weight flow, lb/sec

W_s secondary weight flow, lb/sec

W_t tertiary weight flow, lb/sec

W_s/W_p secondary weight-flow ratio

W_t/W_p tertiary weight-flow ratio

APPARATUS

Ejector Research Facility

The ejector-research facility shown in figure 1 consists of two concentric ducts simulating an engine tail pipe and a cooling-air passage. For this investigation, a third concentric duct was added to provide a cooling-air passage for the outer shroud. Air was supplied from the laboratory air-supply system to these ducts, as shown, and was passed through the primary nozzle and the cooling-air passages into the exhaust chamber. The air was supplied at a pressure of 40 pounds per square inch gage, a temperature of approximately 80° F, and a dew point of -20° F. The exhaust chamber was connected to the laboratory exhaust system so that the ejector exit pressure could be varied from atmospheric to about 2 pounds per square inch absolute.

The primary, secondary, and tertiary air flows were measured by means of standard A.S.M.E. sharp-edge orifices. The total pressures and temperatures were measured with total-pressure tubes and single, bare-wire, iron-constantan thermocouples, respectively. The primary measuring station, located 20 inches upstream of the primary-nozzle exit, consisted of two total-pressure tubes, two wall static taps, and one thermocouple. The total-pressure tubes and the thermocouple projected about one-third of the duct diameter into the stream, because surveys had shown that measurements at this location gave the average of the total-pressure profile. The secondary instrumentation, consisting of two total pressure tubes and one thermocouple, was located at a station about $27\frac{1}{2}$ inches upstream of the primary-nozzle exit. This instrumentation was duplicated for the tertiary stream at a station about $1\frac{1}{8}$ inches upstream of the primary-nozzle exit. The ejector exit pressure was measured in the exit plane of the outer shroud by means of two static-pressure tubes attached to the outside wall of the outer shroud.

The lower portion of the facility is connected to the laboratory-air supply system by means of flexible bellows and is pivoted to a steel frame in order that the axial force may be freely transmitted to a null-type balanced-pressure diaphragm, thrust-measuring cell. The output pressure of this cell is directly proportional to the applied force and, hence, is a direct measure of the resultant force acting on the ejector in an axial direction. In order that the force on the thrust cell would always be in one direction, an axial preload force, consisting of a counterweight connected to the rig by large pulleys and steel tapes, was applied to the thrust cell.

Ejector Models

In this investigation two conical nozzles having areas equivalent
to a specific manufacturer's iris-type variable-area nozzle in the open
and closed positions were used. The relative location of the shrouds
with respect to the two primary nozzles is shown in figure 2. The open
and closed primary nozzles had exit diameters of 4.79 and 3.49 inches,
respectively, and the corresponding half-cone angles were $2^\circ 57'$ and $20^\circ 35'$.
The inside diameter of the approach pipe to the primary nozzles was
5 inches. The inner shroud was essentially cylindrical and had an exit
diameter of 5.65 inches. The conical outer shroud had an exit diameter
of 6.30 inches and a half-cone angle of $7^\circ 18'$. The spacing and diameter
ratios for both configurations are shown in the table in figure 2.

PROCEDURE

Each of the two primary nozzles was calibrated to determine the
flow coefficients and the primary nozzle thrust over a range of pressure
ratios from 1.0 to 10. The various primary pressure ratios were obtained
by throttling the inlet air and by reducing the ambient pressure in the
exhaust chamber. With the shrouds in place, the investigation of each
complete double-shroud ejector configuration consisted of four phases.
The first phase was an investigation of the performance over a range of
primary pressure ratios from 1.0 to 10 with the shroud-inlet passages
blocked (zero secondary and tertiary air flow). The second phase con-
sisted in determining the tendency for backflow to occur in either of
the two cooling-air passages and the magnitude of such flow. In order
to accomplish this, the duct controlling the total air flow to the two
cooling-air passages was blocked while the valves interconnecting the
secondary and tertiary systems were open so as to allow air to circulate
through the two interconnected systems.

The third phase was an investigation of the interaction and conse-
quent sensitivity of each cooling-air system to the other. This phase
was conducted at a constant primary pressure ratio of about 3.0; while
the tertiary weight flow ratio, and hence the tertiary pressure ratio,
was varied over a range of values, and the secondary weight flow ratio
was so varied as to maintain a constant secondary pressure ratio of 1.30.
In this way the effect of tertiary flow on the secondary weight-flow
ratio was determined. The effect of secondary flow on the tertiary
weight-flow ratio was determined in a similar manner; that is, by
varying the secondary weight-flow ratio while a constant tertiary
pressure ratio of 1.30 was being maintained.

The final phase was that of determining the pumping and thrust characteristics for a range of constant primary pressure ratios from 1.10 to 9.5. This phase was conducted with the total pressures in the two cooling passages approximately equal, so as to simulate a common inlet and plenum chamber for the two cooling-air passages. Although ejector performance was determined with 80° F primary, secondary, and tertiary air, the weight flow ratios presented herein are multiplied by $\sqrt{T_s/T_p}$ and $\sqrt{T_t/T_p}$ as a reminder that the application of these data to hot jet installations requires a temperature correction.

The axial force transmitted to the thrust cell was composed of the ejector thrust force, the pressure-area force imposed on the system by the difference between atmospheric pressure and the ejector exit pressure in the exhaust chamber, and the axial preload force. The pressure-area force was determined from a calibration over the range of ejector-exit pressures used in the investigation. The ejector thrust was obtained by subtracting the force acting on the thrust cell from the sum of the preload and the pressure-area forces. In order that the thrust data be consistent and accurate, the pressure-area force-calibration curve was checked daily throughout the investigation.

RESULTS AND DISCUSSION

Zero Secondary and Tertiary Flow

Performance. - The performance of the closed and the open primary-nozzle configurations with zero secondary and tertiary air flow is shown in figures 3(a) and 3(b) and in table I. The effect of primary pressure ratio on secondary pressure ratio is typical of single-shroud cylindrical ejectors having diameter and spacing ratios similar to those used in this investigation. The effect of primary pressure ratio on tertiary pressure ratio is typical of that of single-shroud conical ejectors having very small spacing ratios; such would be the case if the inner shroud were considered the primary nozzle and the spacing were the distance from the exit of the inner shroud to the exit of the outer shroud.

It should be noted that the curve of secondary pressure ratio in figure 3(a) exhibits a marked amount of hysteresis and the tertiary pressure ratio curve shows a slight amount of hysteresis in the primary pressure ratio range from 3.5 to 5.0 as indicated by the arrows on the curves. This phenomenon has previously been encountered with cylindrical ejectors having large diameter ratios and small spacing ratios, as shown in reference 1, but has not been observed for small diameter ratios. Hysteresis occurs because the primary jet remains attached to the shroud wall until the primary pressure ratio is decreased to a value less than that at which attachment first occurred as the primary pressure ratio

was being increased. The jet finally becomes detached at this lower primary pressure ratio, and the shroud pressures assume their normal values. A further discussion of this hysteresis may be found in reference 1.

Thrust characteristics. - The effect of primary pressure ratio on gross thrust ratio for zero secondary and tertiary air flow is presented in figure 4(a) for the closed primary-nozzle configuration and in figure 4(b) for the open primary-nozzle configuration. Gross thrust ratio is defined as the ratio of ejector gross thrust F_{ej} to the primary nozzle (ejector shrouds removed) gross thrust F_j at the same primary pressure ratio. Ejector gross thrust F_{ej}, then, includes the combined thrust produced by the mass flow through the cooling-air passages, and the primary-nozzle gross thrust F_j includes only the thrust produced by the mass flow through the primary nozzle.

The thrust characteristics with the closed-nozzle configuration (fig. 4(a)) exhibit hysteresis similar to that for the secondary pressure ratio (fig. 3(a)), and indicate that a loss in gross thrust of as much as 33 percent of primary-nozzle gross thrust is possible with this configuration when the cooling-air flow is zero. Hysteresis did not occur for the open primary-nozzle configuration with zero cooling-air flow (fig. 4(b)); the greatest loss in gross thrust occurred at a primary pressure ratio of 2.0 and amounted to about 17 percent of the primary-nozzle gross thrust.

A comparison of figures 4(b) and 3(b) shows that the minimum gross thrust ratio occurred at the primary pressure ratio for which the secondary pressure ratio was a minimum, and that a slight dip occurred in the gross-thrust-ratio curve at the primary pressure ratio for which the tertiary pressure ratio was a minimum. This phenomenon may be attributed to shock losses accompanying the overexpansion of the primary jet. A more complete discussion of the effects of overexpansion and shock losses on ejector thrust may be found in reference 2.

A further comparison of figures 4(a) and 4(b) indicates that with zero secondary and tertiary flow, the gross thrust was higher with the open primary-nozzle configuration (small diameter ratio). This relation is consistent with the trends indicated by the data of reference 2.

Effect of Primary Pressure Ratio on Backflow

In order for backflow to occur in one of the two cooling-air passages, the pressure in one passage must be higher than the pressure in the other. An inspection of figures 3(a) and 3(b) indicates the regions of primary

2765

pressure ratio in which backflow will occur. That is, for the regions in which the secondary pressure ratio curve lies below the tertiary pressure ratio curve, (secondary pressure ratio is less than tertiary pressure ratio in figs. 3(a) and 3(b)), the circulation of air is in the normal direction through the secondary passage and is reversed through the tertiary system. For the opposite conditions of secondary and tertiary pressure ratio, the circulation is reversed.

The effect of primary pressure ratio on backflow is shown in figures 5(a) and 5(b) and in table II for the closed and the open primary nozzles. The magnitude of the backflow, although measurable, was very small; less than 0.2 percent of primary air flow through the closed-nozzle configuration, and slightly exceeding 0.4 percent of primary air flow for the open-nozzle configuration. This test simulated a common inlet plenum chamber for the two cooling-air passages with no external source of air; the positive portion of each curve therefore indicates circulation in the normal direction through the secondary passage and in a reverse direction through the tertiary system. The negative portion of the curve indicates circulation in the opposite direction, with back-flow occurring through the secondary system and flow in the normal direction existing in the tertiary passage. The direction of the circulation flow for each configuration reverses (magnitude of backflow becomes zero) at approximately the same primary pressure ratios at which the value of primary and secondary pressure ratio become equal (figs. 3(a) and 3(b)). It should be noted that the data of figure 5(a) were obtained in the direction of increasing primary pressure ratio, and thus any effect of hysteresis on backflow is not included.

Interaction of Secondary and Tertiary Systems

Investigation of the interaction between the secondary and tertiary flow systems indicated that there was little interaction between the two systems. The weight flow through each shroud was insensitive to changes through the other, as shown in table III and in figures 6 to 9 for the closed and the open primary nozzles. For a primary pressure ratio of about 3.0 and a secondary pressure ratio of about 1.3, with the primary nozzle in the closed position, the secondary weight-flow ratio was essentially independent of the tertiary weight-flow ratio as the tertiary weight-flow-ratio increased from 0.02 to 0.15 (fig. 6). Likewise, while varying the secondary weight-flow ratio with the primary nozzle closed, the tertiary weight-flow ratio was essentially constant for a constant tertiary pressure ratio of about 1.3 (fig. 7). Similar results were obtained for the open primary-nozzle configuration (figs. 8 and 9). Although this effect was investigated only at a primary pressure ratio of about 3.0, it is believed that these characteristics are representative of those which would be obtained at other primary pressure ratios.

Ejector Performance

Pumping characteristics. - The pumping characteristics of the double-shroud ejector configuration with the closed primary nozzle are presented in figure 10 for several primary pressure ratios from 1.10 to 9.5, and are tabulated in table IV. As mentioned previously, the total pressures in the two cooling passages were maintained approximately equal for this phase of the investigation. The effect of secondary pressure ratio on secondary weight-flow ratio is shown in figure 10(a), and the corresponding tertiary-system pumping characteristics are shown in figure 10(b). A comparison of the two figures discloses that the pumping ability of the secondary and the tertiary systems are nearly identical. It is evident from these data that at low primary pressure ratios secondary and tertiary weight-flow ratios were extremely sensitive to variations in secondary and tertiary pressure ratios. As the primary pressure ratio was increased this sensitivity of secondary and tertiary flow became less pronounced.

The secondary and the tertiary weight-flow ratios with the open primary nozzle are shown in figures 11(a) and 11(b), respectively, and in table IV. A comparison of these figures reveals that the secondary outperforms the tertiary system at the lower primary pressure ratios over the entire range of secondary and tertiary pressure ratio, and at primary pressure ratios of 3.0 and 4.0 at the lower secondary and tertiary pressure ratios. For the three highest primary pressure ratios investigated (6.0, 8.0, and 9.5), the tertiary system pumps a far greater amount of air than the secondary. Again, the sensitivity of the weight-flow ratios to changes in secondary and tertiary pressure ratio decreased greatly with increasing primary pressure ratio.

A comparison of figures 10 and 11 shows that, for a given primary pressure ratio, the weight-flow ratios for the open primary-nozzle configuration are, in general, considerably lower than for the closed-primary configuration. This comparison also discloses, as pointed out in reference 8, that for the closed primary-nozzle configuration (large diameter ratio), the secondary and tertiary weight-flow ratios were more sensitive to changes in secondary and tertiary pressure ratio for any particular primary pressure ratio, than for the open primary-nozzle configuration (small diameter ratio). The open primary-nozzle configuration will, however, pump secondary and tertiary air over a wider range of secondary and tertiary pressure ratios and will start pumping at a lower primary pressure ratio. These comparisons indicate that ejector performance is not compatible with afterburner-cooling requirements, in that there is a great excess of air for the nonafterburning (closed primary nozzle) condition. Also, because the required tertiary flow is generally about one-fifth that required for the secondary system, there is a great excess of tertiary air for most conditions. As pointed out in reference 8, such an excess of tertiary air flow can be reduced by decreasing the

tertiary diameter and spacing ratios to values slightly larger than the secondary diameter and spacing ratios.

Thrust characteristics. - The effect of secondary and tertiary pressure ratio on gross thrust ratio is shown in table IV and in figures 12(a) and 12(b) for the closed and open primary-nozzle configurations, respectively. For the closed-primary nozzle, a gain in gross thrust was obtained for all primary pressure ratios, although with primary pressure ratios of 8.0 and 9.5 there was a loss in gross thrust at secondary and tertiary pressure ratios below about 1.0. These losses were as much as 4 percent and $4\frac{1}{2}$ percent, respectively, at the primary pressure ratios of 8.0 and 9.5. Data for a primary pressure ratio of 1.10 indicated that a gain in gross thrust of about 34 percent was obtainable, which was due, in most part, to the relatively large mass flow through the secondary and tertiary systems. Data for the open nozzle (fig. 12(b)) also show that a gross thrust gain is obtainable for all primary pressure ratios, with losses occurring at the low secondary and tertiary pressure ratios for primary pressure ratios of 1.10, 1.50, 4.0, and 6.0.

A comparison of figures 12(a) and 12(b) reveals the same general thrust trends that were observed in the earlier investigation of double-shroud ejectors (reference 8). These curves also follow the same general trends as the weight-flow curves in figures 10 and 11; namely, that for any given primary pressure ratio, the thrust curves for the closed primary nozzle lie above those of the open-nozzle configuration. This is due, in part, to the greater secondary and tertiary mass flows at given secondary and tertiary pressure ratios for the closed primary-nozzle configuration. Also the greater expansion ratio of the closed primary nozzle would contribute to higher thrust ratios at the high primary pressure ratios. Although the higher thrust ratios were obtained with the closed primary-nozzle configuration, it does not necessarily follow that this is the best configuration, in view of the large amount of secondary and tertiary air that is being pumped.

The sensitivity of the gross thrust ratio to changes in secondary and tertiary pressure ratio is, in general, less for the open primary-nozzle configuration. Furthermore, for each configuration this sensitivity to secondary and tertiary pressure ratio decreases as the primary pressure ratio increases.

Application of Data

As pointed out in reference 8, the performance of an ejector in an actual installation will depend upon the performance of the ejector itself as a pump and upon the performance of the cooling-air flow system for a range of operating conditions. Also, a correction must be applied to the

weight-flow ratios to take into consideration the ratio of cooling-air
temperature to engine-gas temperature, as described in reference 3.
However, this correction may not be valid under all conditions, particu-
larly at the high temperature ratios; some error may therefore result,
as indicated in reference 4. However, the comparisons of full-scale
and model-ejector data shown in this reference are believed to show
greater discrepancies than would have been the case had the configurations
been exact scale models of the ejectors used. Until more complete high-
temperature ejector data are available, the data presented herein should
give an indication of trends to be expected from double-shroud ejectors
having similar configurations and will serve as a supplement to the data
contained in reference 8.

CONCLUDING REMARKS

Data obtained with a double-shroud ejector configuration, using
two different size convergent primary nozzles in order to simulate a
specific manufacturer's variable-area iris-type nozzle in the closed
and in the open positions, indicated that the performance with the cooling-
air passages blocked was typical of that for single ejectors having simi-
lar diameter and spacing ratios. Also indicated was a possible gross
thrust loss of as great as 33 percent of primary-nozzle gross thrust with
the primary nozzle in the closed position and with no cooling-air flow.
For the open-primary-nozzle configuration and no cooling-air flow, the
thrust losses were reduced to 17 percent of primary-nozzle gross thrust.
For both configurations the magnitude of backflow was relatively small.
There was very little interaction between the secondary and tertiary
flow systems as each system was essentially unaffected by changes in
flow through the other. A comparison of the pumping characteristics for
both configurations indicates that, in general, the closed primary-nozzle
configuration is capable of pumping more cooling air; whereas the open-
nozzle configuration will pump over a greater range of secondary and
tertiary pressure ratios.

Lewis Flight Propulsion Laboratory
        National Advisory Committee for Aeronautics
                Cleveland, Ohio

REFERENCES

1. Kochendorfer, Fred D., and Rousso, Morris D.: Performance Charac-
        teristics of Aircraft Cooling Ejectors Having Short Cylindrical
        Shrouds. NACA RM E51E01, 1951.

2765

2. Ellis, C. W., Hollister, D. P., and Sargent, A. F., Jr.: Preliminary Investigation of Cooling-Air Ejector Performance at Pressure Ratios from 1 to 10. NACA RM E51H21, 1951.

3. Wilsted, H. D., Huddleston, S. C., and Ellis, C. W.: Effect of Temperature on Performance of Several Ejector Configurations. NACA RM E9E16, 1949.

4. Wallner, Lewis E., and Jansen, Emmert T.: Full-Scale Investigation of Cooling Shroud and Ejector Nozzle for a Turbojet Engine - Afterburner Installation. NACA RM E51J04, 1951.

5. Greathouse, W. K., and Hollister, D. P.: Preliminary Air-Flow and Thrust Calibrations of Several Conical Cooling-Air Ejectors with a Primary to Secondary Temperature Ratio of 1.0. I - Diameter Ratios of 1.21 and 1.10. NACA RM E52E21, 1952.

6. Greathouse, W. K., and Hollister, D. P.: Preliminary Air-Flow and Thrust Calibrations of Several Conical Cooling-Air Ejectors with a Primary to Secondary Temperature Ratio of 1.0. II - Diameter Ratios of 1.06 and 1.40. NACA RM E52F26, 1952.

7. Huddleston, S. C., Wilsted, H. D., and Ellis, C. W.: Performance of Several Air Ejectors with Conical Mixing Sections and Small Secondary Flow Rates. NACA RM E8D23, 1948.

8. Ellis, C. W., Hollister, D. P., and Wilsted, H. D.: Investigation of Performance of Several Double-Shroud Ejectors and Effect of Variable-Area Exhaust Nozzle on Single Ejector Performance. NACA RM E52D25, 1952.

TABLE I - PERFORMANCE WITH ZERO SECONDARY AND TERTIARY FLOW

Run	Primary-stream total pressure P_p (in. mercury absolute)	Secondary-stream total pressure P_s (in. mercury absolute)	Tertiary-stream total pressure P_t (in. mercury absolute)	Ambient exhaust pressure p_0 (in. mercury absolute)	Primary weight flow W_p (lb/sec)	Secondary weight flow W_s (lb/sec)	Tertiary weight flow W_t (lb/sec)	Gross thrust of primary nozzle with shrouds removed F_j (lb) (a)	Gross thrust of ejector F_{ej} (lb)	Primary-stream total temperature T_p (°R)	Secondary-stream total temperature T_s (°R)	Tertiary-stream total temperature T_t (°R)	Primary pressure ratio P_p/p_0	Secondary pressure ratio P_s/p_0	Tertiary pressure ratio P_t/p_0	Secondary weight-flow ratio $\frac{W_s}{W_p}\sqrt{\frac{T_s}{T_p}}$	Tertiary weight-flow ratio $\frac{W_t}{W_p}\sqrt{\frac{T_t}{T_p}}$	Gross thrust ratio F_{ej}/F_j
							Primary-nozzle position, closed											
1	30.19	14.94	14.96	14.99	2.88	0	0	97.9	107.4	551.0	---	---	2.014	0.9947	0.9907	0	0	1.097
2	30.34	12.00	11.90	12.06	3.02	0	0	118.5	121.1	551.0	---	---	2.518	.9969	.9976	0	0	1.025
3	30.59	9.79	9.75	9.80	3.03	0	0	126.9	130.8	551.0	---	---	3.090	.9869	.9848	0	0	1.030
4	34.84	9.77	9.75	9.85	3.44	0	0	149.1	156.6	551.0	---	---	3.471	.9818	.9779	0	0	1.049
5	38.89	9.49	9.59	9.65	3.97	0	0	174.5	178.6	551.0	---	---	3.958	.9854	.9774	0	0	1.024
6	44.84	9.17	9.66	9.96	4.50	0	0	207.6	209.0	551.5	---	---	4.507	.9815	.9709	0	0	1.007
7	43.09	3.82	9.81	10.22	4.94	0	0	230.3	182.0	552.0	---	---	4.803	.3798	.9599	0	0	.7905
8	50.29	3.88	9.53	9.84	5.06	0	0	258.4	182.0	551.5	---	---	5.028	.3915	.9588	0	0	.806
9	53.29	4.21	9.54	9.96	5.54	0	0	245.4	221.1	552.0	---	---	5.557	.4251	.9588	0	0	.529
10	45.62	8.01	9.44	9.78	4.55	0	0	212.7	213.5	547.0	---	---	4.560	.8998	.9542	0	0	1.003
11	47.07	3.50	10.18	10.69	4.78	0	0	217.2	149.6	549.0	---	---	4.445	.3304	.9613	0	0	.7498
12	40.23	3.03	9.76	10.17	4.06	0	0	140.3	124.0	549.0	---	---	3.958	.3973	.9597	0	0	.7100
13	38.17	2.89	9.61	10.04	3.84	0	0	137.9	108.2	549.0	---	---	3.803	.2978	.9572	0	0	.8680
14	35.02	9.34	9.33	9.57	3.52	0	0	185.6	186.0	549.0	---	---	3.659	.9760	.9742	0	0	1.009
15	45.17	8.96	9.49	9.65	4.55	0	0	209.9	209.7	549.0	---	---	4.569	.9118	.9864	0	0	.9968
16	47.32	9.45	9.46	9.62	4.80	0	0	222.2	217.9	549.0	---	---	4.819	.9855	.9855	0	0	.9798
17	48.62	7.85	9.48	9.88	4.92	0	0	229.3	230.4	549.0	---	---	4.921	.8047	.9596	0	0	.9615
18	49.87	3.70	8.97	10.39	5.06	0	0	232.8	180.6	549.0	---	---	4.781	.3561	.9598	0	0	.7757
19	49.42	3.65	9.47	9.88	5.01	0	0	233.6	184.9	549.0	---	---	5.002	.3674	.9588	0	0	.7908
20	55.47	4.03	9.34	9.80	5.82	0	0	268.5	222.5	549.0	---	---	5.680	.4112	.9631	0	0	.8287
21	59.97	4.34	9.57	10.07	6.09	0	0	292.7	247.4	549.8	---	---	5.965	.4310	.9605	0	0	.8451
22	65.92	4.74	9.15	9.77	6.64	0	0	327.8	285.1	548.9	---	---	6.747	.4858	.9388	0	0	.9596
23	70.87	5.20	9.15	9.82	7.13	0	0	358.1	319.9	548.0	---	---	7.108	.5092	.9312	0	0	.9306
24	70.17	5.01	8.40	9.90	7.10	0	0	384.8	317.1	549.0	---	---	7.827	.5446	.9150	0	0	.8942
25	74.47	5.55	8.02	9.28	7.48	0	0	384.5	350.8	549.0	---	---	8.155	.5744	.8842	0	0	.8150
26	78.57	5.51	8.42	8.50	7.62	0	0	347.6	365.4	549.0	---	---	8.867	.8247	.7853	0	0	.8120
27	75.57	5.58	5.43	8.10	7.85	0	0	390.4	388.3	549.0	---	---	9.330	.6494	.6704	0	0	.8192
28	75.97	5.26	4.96	7.80	7.88	0	0	394.2	352.8	549.0	---	---	9.740	.6789	.6368	0	0	.3197
29	77.37	8.56	6.89	7.57	7.81	0	0	405.1	389.7	549.0	---	---	10.22	.7081	.6198	0	0	.3171
30	52.77	9.41	9.55	9.65	5.50	0	0	140.9	145.0	548.0	---	---	3.629	.9843	.9791	0	0	1.089
31	29.97	9.58	9.77	9.97	3.02	0	0	125.1	126.1	547.5	---	---	3.006	.9880	.9799	0	0	1.016
							Primary-nozzle position, open											
1	29.95	26.01	27.05	27.25	3.90	0	0	45.4	44.08	539.0	---	---	1.099	0.9553	0.9934	0	0	0.9688
2	30.08	22.07	23.82	24.11	5.25	0	0	95.1	86.55	536.0	---	---	1.246	.9154	.9880	0	0	.9628
3	28.95	17.47	19.56	19.91	5.80	0	0	141.7	125.6	537.0	---	---	1.503	.8774	.9834	0	0	.8882
4	30.45	14.61	16.77	17.18	5.98	0	0	175.6	167.5	537.0	---	---	1.788	.8417	.9798	0	0	.9554
5	30.13	12.08	15.15	15.90	5.94	0	0	190.7	176.5	538.0	---	---	1.944	.7774	.9774	0	0	.8541
6	30.15	11.14	14.70	15.12	5.95	0	0	184.4	179.2	538.0	---	---	1.991	.7345	.9748	0	0	.8230
7	30.18	8.27	14.46	14.85	5.95	0	0	198.8	188.0	538.0	---	---	2.021	.4800	.9685	0	0	.8583
8	30.85	5.48	13.18	13.42	5.94	0	0	209.9	179.5	538.0	---	---	2.253	.6045	.9608	0	0	.8573
9	30.95	5.37	11.65	11.90	5.82	0	0	218.9	197.7	558.0	---	---	2.589	.6513	.9710	0	0	.9090
10	30.98	6.34	9.65	10.10	5.85	0	0	226.4	218.9	538.0	---	---	3.078	.5387	.9735	0	0	.9821
11	40.68	6.98	9.84	9.83	7.88	0	0	348.2	353.5	539.0	---	---	4.038	.7029	.9577	0	0	.9436
12	48.85	8.84	9.29	9.82	9.82	0	0	455.8	444.4	540.0	---	---	5.025	.5587	.9542	0	0	.9796
13	54.45	9.27	9.26	10.16	10.58	0	0	500.8	486.9	540.0	---	---	5.347	.9104	.9066	0	0	.9788
14	54.43	9.21	6.35	6.48	10.88	0	0	512.5	498.4	540.5	---	---	6.072	1.098	.7894	0	0	.9776
15	54.85	9.25	4.96	4.96	10.76	0	0	523.5	508.2	541.5	---	---	6.705	1.151	.6061	0	0	.9671
16	54.93	9.23	4.56	7.46	10.76	0	0	531.1	519.7	541.0	---	---	7.575	1.259	.6328	0	0	.9784
17	55.03	9.26	4.55	4.70	10.80	0	0	539.2	531.1	541.0	---	---	8.213	1.382	.6781	0	0	.9680
18	55.05	9.94	4.48	6.10	10.77	0	0	544.6	540.4	541.5	---	---	9.081	1.515	.7311	0	0	.9921
19	56.65	9.54	4.48	5.34	10.86	0	0	547.7	546.7	541.5	---	---	10.62	1.735	.6275	0	0	.9891
20	55.45	9.54	4.42	4.85	10.88	0	0	550.7	550.3	541.5	---	---	11.84	1.893	.6848	0	0	1.001
21	54.75	9.59	4.80	7.88	10.96	0	0	536.5	525.1	541.5	---	---	7.089	1.190	.8054	0	0	.9775
22	55.75	9.35	4.39	8.30	10.68	0	0	536.0	580.5	540.5	---	---	8.714	1.137	.6019	0	0	.9781
23	55.89	6.95	5.15	8.30	10.59	0	0	505.4	484.1	540.0	---	---	8.413	1.076	.6161	0	0	.9775
24	53.58	9.01	6.89	8.81	10.41	0	0	501.8	487.7	540.0	---	---	8.048	1.023	.7480	0	0	.9718
25	55.08	9.98	8.92	9.71	10.38	0	0	490.4	441.5	538.5	---	---	5.467	.9258	.8680	0	0	.9615
26	55.15	9.10	9.96	10.66	10.35	0	0	482.4	472.6	559.5	---	---	4.989	.8845	.8371	0	0	.9801
27	55.85	9.18	11.18	11.70	10.59	0	0	473.8	463.8	559.5	---	---	4.580	.7845	.8630	0	0	.9786
28	55.15	9.17	13.14	13.68	10.35	0	0	443.6	443.0	538.5	---	---	5.901	.6735	.8848	0	0	.9743
29	40.93	7.05	11.54	11.90	7.80	0	0	388.8	514.3	538.5	---	---	5.381	.5855	.8672	0	0	.9651
30	40.15	7.08	14.11	14.48	7.81	0	0	306.0	280.6	538.5	---	---	2.778	.4896	.9794	0	0	.9706
31	30.18	6.47	13.02	13.26	5.90	0	0	310.4	196.6	538.5	---	---	2.879	.4119	.9604	0	0	.8895
32	30.18	6.18	14.46	14.88	5.91	0	0	166.9	186.7	538.5	---	---	2.087	.4137	.9711	0	0	.8417
33	30.15	11.67	15.01	15.38	5.91	0	0	179.0	181.5	558.5	---	---	1.962	.7846	.9772	0	0	.9444
34	30.18	14.51	14.86	17.20	5.90	0	0	177.1	162.0	538.2	---	---	1.784	.8456	.9797	0	0	.9475
35	30.93	8.42	14.72	15.19	5.90	0	0	194.7	161.4	538.2	---	---	1.990	.4926	.9791	0	0	.8298

a Values obtained from nozzle calibration.

TABLE II – EFFECT OF PRIMARY PRESSURE RATIO ON BACKFLOW

Run	Primary-stream total pressure P_p (in. mercury absolute)	Secondary-stream total pressure P_s (in. mercury absolute)	Tertiary-stream total pressure P_t (in. mercury absolute)	Ambient exhaust pressure P_0 (in. mercury absolute)	Primary weight flow W_p (lb/sec)	Secondary weight flow W_s (lb/sec) (a)	Tertiary weight flow W_t (lb/sec) (a)	Gross thrust of primary nozzle with shrouds removed F_j (lb) (b)	Gross thrust of ejector F_{ej} (lb)	Primary-stream total temperature T_p (°R)	Secondary-stream total temperature T_s (°R)	Tertiary-stream total temperature T_t (°R)	Primary pressure ratio P_p/P_0	Secondary pressure ratio P_s/P_0	Tertiary pressure ratio P_t/P_0	Secondary weight-flow ratio $\frac{W_s}{W_p}\sqrt{\frac{T_s}{T_p}}$ (a)	Tertiary weight flow ratio $\frac{W_t}{W_p}\sqrt{\frac{T_t}{T_p}}$ (a)	Gross thrust ratio F_{ej}/F_j
									Primary-nozzle position, closed									
1	30.21	26.68	26.70	26.81	1.72	-0.00111	0.00111	24.64	24.17	538.0	540.0	542.0	1.127	0.9962	0.9959	-0.00085	0.00085	0.9807
2	29.71	23.71	23.76	23.87	2.20	-.00249	.00249	40.70	41.95	538.0	541.0	541.0	1.245	.9933	.9954	-.00115	.00115	1.031
3	29.81	19.58	19.64	19.78	2.87	-.00387	.00387	68.06	72.52	538.0	542.0	541.0	1.312	.9899	.9929	-.00145	.00145	1.065
4	29.85	17.07	17.17	17.29	2.78	-.00364	.00384	82.86	90.30	538.0	542.0	541.0	1.727	.9873	.9927	-.00131	.00131	1.077
5	30.11	14.66	14.97	15.08	2.92	-.00322	.00522	97.05	104.5	538.0	540.0	540.0	1.997	.9854	.9908	-.00082	.00082	1.088
6	29.61	11.78	11.84	11.95	2.97	-.00244	.00244	112.6	122.3	538.0	538.0	536.0	2.495	.9822	.9801	-.00064	.00064	1.048
7	29.91	9.92	10.0	10.10	2.97	-.00251	.00251	122.2	126.0	538.0	542.0	538.0	2.961	.9533	.9736	-.00040	.00040	1.038
8	40.31	9.59	9.59	9.86	4.00	.00706	-.00706	182.3	189.1	539.0	543.0	538.0	4.092	.9671	.9318	.00159	-.00159	.9859
9	50.06	8.01	9.60	10.03	5.08	.0121	-.0121	236.7	258.8	538.0	536.0	531.0	4.991	.7986	.9571	.00198	-.00198	.8775
10	60.16	4.79	9.15	9.82	6.09	.0118	-.0118	294.9	268.8	538.0	531.0	532.0	6.126	.4878	.9081	.00196	-.00196	.9044
11	70.56	5.39	9.09	10.01	7.12	.00758	-.00758	352.6	319.2	539.0	532.0	530.0	7.049	.5385	.8501	.00095	-.00095	.9108
12	78.81	5.98	8.21	9.88	7.98	.00559	-.00559	400.3	384.7	539.0	543.0	528.0	7.989	.6018	.7101	.00069	-.00069	.9121
13	79.81	5.78	6.37	8.97	8.08	.00569	-.00559	409.2	373.3	539.0	543.0	527.0	8.875	.6444	.6400	.00050	-.00050	.9293
14	80.01	5.58	5.21	8.14	8.12	-.00408	.00408	415.4	386.1	559.0	543.0	526.0	9.828	.6818	.5818	-.00050	.00050	.8270
15	79.76	5.50	4.99	7.75	8.10	-.00524	.00524	415.7	385.4	559.0	542.0		10.26	.7086	.6450	-.00065	.00065	
									Primary-nozzle position, open									
16	30.03	26.10	27.01	27.18	3.98	0.0154	-0.0154	49.06	44.79	550.0	548.0	543.0	1.106	0.9603	0.9937	0.0039	-0.0039	0.9131
17	30.08	22.56	23.90	24.20	5.15	.0185	-.0185	92.23	88.68	548.0	547.0	543.0	1.243	.9240	.9878	.0036	-.0036	.9640
18	29.98	17.90	19.84	20.20	5.75	.0190	-.0190	139.1	128.7	547.0	548.0	543.0	1.484	.8861	.9822	.0035	-.0035	.9252
19	29.89	14.85	14.89	17.28	5.76	.0179	-.0179	170.2	182.1	546.0	544.0	543.0	1.731	.8592	.9786	.0031	-.0031	.9522
20	30.03	11.89	14.71	15.08	5.81	.0106	-.0186	193.8	182.0	546.0	545.0	543.0	1.991	.7886	.9755	.0032	-.0032	.9391
21	30.13	8.84	13.41	13.78	6.80	.0244	-.0244	206.7	180.6	548.0	546.0	543.0	2.187	.4819	.9751	.0042	-.0042	.8782
22	30.06	6.28	11.59	11.89	5.81	.0205	-.0203	219.0	202.6	546.0	545.0	543.0	2.530	.5282	.9748	.0035	-.0035	.9246
23	29.93	8.05	9.74	10.04	5.77	.0182	-.0162	254.4	221.1	546.0	538.0	543.0	2.981	.6026	.9701	.0026	-.0026	.9433
24	40.23	7.53	9.61	10.01	7.79	.0125	-.0125	347.3	337.7	546.0	538.0	543.0	4.019	.7522	.9600	.0016	-.0016	.9721
25	49.83	8.76	9.48	10.07	9.70	.0058	-.0058	451.4	441.5	546.0	536.0	542.0	4.946	.8699	.9394	.0006	-.0006	.9784
26	50.43	8.42	8.66	8.18	9.82	-.0079	.0079	475.4	472.9	546.0	557.0	542.0	6.165	1.029	.8142	-.0008	.0008	.9846
27	49.63	8.30	8.28	8.99	9.45	0	0	448.3	441.5	546.0	556.0	542.0	5.409	.9232	.9210	0	-.0011	.9751
28	50.53	8.32	5.27	7.35	9.80	-.0108	.0108	462.1	470.0	546.0	556.0	542.0	6.865	1.138	.7190	-.0011	.0011	.9812
29	50.33	8.29	4.65	6.43	9.81	-.0108	.0108	490.4	481.3	546.0	556.0	542.0	7.827	1.289	.7278	-.0011	.0011	.9812
30	50.25	8.28	5.54	5.40	9.81	-.0118	.0118	498.8	495.6	546.0	556.0	542.0	9.302	1.550	1.026	-.0012	.0012	.9836

[a] Negative values indicate backflow.
[b] Values obtained from nozzle calibration.

TABLE III - INTERACTION OF SECONDARY AND TERTIARY SYSTEMS

Run	Primary-stream total pressure P_p (in. mercury absolute)	Secondary-stream total pressure P_s (in. mercury absolute)	Tertiary-stream total pressure P_t (in. mercury absolute)	Ambient exhaust pressure P_0 (in. mercury absolute)	Primary weight flow W_p (lb/sec)	Secondary weight flow W_s (lb/sec)	Tertiary weight flow W_t (lb/sec)	Gross thrust of primary nozzle with shrouds removed F_j (lb) (a)	Gross thrust of ejector F_{ej} (lb)	Primary-stream total temperature T_p (°R)	Secondary-stream total temperature T_s (°R)	Tertiary-stream total temperature T_t (°R)	Primary pressure ratio P_p/P_0	Secondary pressure ratio P_s/P_0	Tertiary pressure ratio P_t/P_0	Secondary weight-flow ratio $\frac{W_s}{W_p}\sqrt{\frac{T_s}{T_p}}$	Tertiary weight flow ratio $\frac{W_t}{W_p}\sqrt{\frac{T_t}{T_p}}$	Gross-thrust ratio F_{ej}/F_j
							Primary-nozzle position, closed											
1	29.96	13.03	10.02	10.0	3.04	0.581	0.068	122.9	127.3	539.0	534.0	530.0	2.996	1.303	1.002	0.1902	0.0189	1.038
2	29.91	13.02	10.11	10.0	3.03	.584	.132	122.7	126.6	539.5	535.5	533.0	2.991	1.302	1.011	.1920	.0453	1.032
3	29.91	13.03	10.27	10.0	3.03	.584	.199	122.6	126.8	540.5	537.5	536.0	2.991	1.303	1.027	.1922	.0684	1.025
4	29.96	13.02	10.52	10.0	3.03	.586	.272	122.9	128.7	541.0	536.5	537.5	2.996	1.302	1.052	.1930	.0896	1.047
5	29.86	13.04	10.93	10.02	3.03	.588	.342	122.3	127.3	542.0	539.0	537.5	2.980	1.301	1.091	.1936	.1124	1.041
6	29.86	13.02	11.59	10.0	3.03	.587	.456	122.4	133.0	542.0	538.0	539.5	2.998	1.302	1.169	.1935	.1499	1.087
7	28.76	10.07	13.03	10.01	3.02	.275	.597	121.7	133.0	542.0	540.0	539.5	2.973	1.000	1.302	.0909	.1972	1.093
8	29.86	10.28	13.03	10.0	3.02	.317	.595	122.3	154.4	544.5	540.5	539.5	2.986	1.026	1.303	.1046	.1961	1.099
9	29.86	10.99	13.04	10.0	3.02	.427	.599	122.3	137.2	545.0	540.5	541.0	2.986	1.099	1.304	.1409	.1975	1.122
10	29.86	13.18	13.05	10.01	3.02	.592	.597	122.3	135.1	545.5	542.5	540.5	2.983	1.317	1.304	.1955	.1968	1.106
11	29.96	9.77	13.01	9.97	3.03	.250	.599	123.1	153.7	545.0	542.0	540.5	3.005	.9799	1.305	.0822	.1967	1.086
12	29.88	9.35	13.03	9.99	3.02	.137	.608	122.4	132.8	546.0	542.0	541.5	2.989	.9339	1.304	.0452	.2009	1.09
							Primary-nozzle position, open											
13	30.12	13.01	10.00	9.98	5.89	0.577	0.0847	257.0	250.3	540.5	541.0	538.0	3.018	1.304	1.002	0.0980	0.0111	1.086
14	30.02	13.05	10.11	10.03	5.89	.581	.1295	255.5	248.9	548.5	545.5	541.5	2.995	1.301	1.008	.1005	.0220	1.057
15	29.87	13.05	10.05	9.89	5.89	.589	.0764	255.0	249.6	542.0	545.5	542.0	2.994	1.304	1.002	.1003	.0130	1.062
16	30.12	13.03	10.21	10.01	5.86	.589	.1961	256.8	251.0	542.0	547.0	543.5	3.009	1.302	1.020	.1006	.0333	1.080
17	29.92	13.04	10.39	10.01	5.87	.590	.2476	254.8	249.6	542.5	547.0	544.0	2.989	1.303	1.037	.1009	.0422	1.054
18	29.97	13.03	10.62	9.99	5.82	.589	.3060	255.2	251.0	541.0	547.0	544.5	3.000	1.304	1.063	.1017	.0528	1.057
19	30.02	13.01	11.17	10.0	5.85	.588	.3991	255.8	254.5	541.0	547.0	544.0	3.002	1.301	1.117	.1010	.0684	1.090
20	30.12	13.05	13.06	10.01	5.87	.588	.6270	256.8	265.1	541.5	547.5	544.0	3.009	1.304	1.305	.1009	.1070	1.111
21	30.06	9.98	12.95	9.97	5.84	.255	.631	256.1	248.9	546.0	542.0	544.0	3.015	.9990	1.299	.0455	.1113	1.054
22	30.09	10.49	13.08	9.96	5.84	.304	.647	256.8	251.0	546.0	544.0	544.0	3.015	1.051	1.303	.0520	.1108	1.061
23	30.09	11.10	13.00	9.98	5.85	.366	.641	256.8	253.1	546.0	544.5	544.0	3.015	1.112	1.303	.0628	.1096	1.069
24	30.09	11.81	13.00	9.99	5.86	.448	.631	256.8	255.7	548.5	547.0	544.0	3.012	1.182	1.301	.0755	.1077	1.086
25	30.09	12.35	13.00	9.98	5.84	.507	.626	256.8	257.4	547.0	547.5	544.0	3.015	1.237	1.303	.0868	.1072	1.088
26	30.14	13.04	13.00	9.98	5.80	.587	.617	257.2	260.9	547.0	548.0	544.0	3.020	1.307	1.303	.1014	.1068	1.100
27	30.14	13.45	13.01	9.99	5.68	.651	.612	257.0	262.4	547.0	549.5	546.0	3.017	1.346	1.302	.1115	.1047	1.107

[a] Values obtained from nozzle calibration.

TABLE IV - EJECTOR PERFORMANCE

Run	Primary-stream total pressure P_p (in. mercury absolute)	Secondary-stream total pressure P_s (in. mercury absolute)	Tertiary-stream total pressure P_t (in. mercury absolute)	Ambient exhaust pressure p_0 (in. mercury absolute)	Primary weight flow W_p (lb/sec)	Secondary weight flow W_s (lb/sec)	Tertiary weight flow W_t (lb/sec)	Gross thrust of primary nozzle with shrouds removed F_j (lb) (a)	Gross thrust of ejector F_{ej} (lb)	Primary-stream total temperature T_p (°R)	Secondary-stream total temperature T_s (°R)	Tertiary-stream total temperature T_t (°R)	Primary pressure ratio P_p/p_0	Secondary pressure ratio P_s/p_0	Tertiary pressure ratio P_t/p_0	Secondary weight-flow ratio $\frac{W_s}{W_p}\sqrt{\frac{T_s}{T_p}}$	Tertiary weight-flow ratio $\frac{W_t}{W_p}\sqrt{\frac{T_t}{T_p}}$	Gross-thrust ratio F_{ej}/F_j
								Primary-nozzle position, closed										

The remainder of the table consists of numerical data (71 runs) that is too faint and low-resolution to transcribe reliably.

a Values obtained from nozzle calibration.

TABLE IV - Concluded. EJECTOR PERFORMANCE

Run	Primary-stream total pressure P_p (in. mercury absolute)	Secondary-stream total pressure P_s (in. mercury absolute)	Tertiary-stream total pressure P_t (in. mercury absolute)	Ambient exhaust pressure p_0 (in. mercury absolute)	Primary weight flow W_p (lb/sec)	Secondary weight flow W_s (lb/sec)	Tertiary weight flow W_t (lb/sec)	Gross thrust of primary nozzle with shrouds removed F_j (lb) (a)	Gross thrust of ejector F_{ej} (lb)	Primary-stream total temperature T_p (°R)	Secondary-stream total temperature T_s (°R)	Tertiary-stream total temperature T_t (°R)	Primary pressure ratio P_p/p_0	Secondary pressure ratio P_s/p_0	Tertiary pressure ratio P_t/p_0	Secondary weight flow ratio $\frac{W_s}{W_p}\sqrt{\frac{T_s}{T_p}}$	Tertiary weight flow ratio $\frac{W_t}{W_p}\sqrt{\frac{T_t}{T_p}}$	Gross-thrust ratio F_{ej}/F_j
								Primary-nozzle position, open										
1	30.19	27.06	27.06	27.12	3.60	0.250	0	29.54	46.2	555.0	549.0	548.0	1.115	0.9969	0.9965	0.0492	0	0.8725
2	30.19	27.19	27.20	27.16	3.64	.305	.129	54.67	45.5	553.0	549.5	549.5	1.112	1.001	1.001	.0659	.0545	.8635
3	30.04	27.19	27.17	27.10	3.48	.343	.168	50.98	44.6	554.0	550.0	551.0	1.108	1.006	1.008	.0982	.0482	.8539
4	30.24	27.31	27.31	27.18	3.53	.384	.224	59.71	46.9	554.5	551.0	552.0	1.113	1.005	1.005	.1113	.0634	.8897
5	30.08	27.32	27.32	27.10	3.50	.454	.284	51.94	47.6	555.0	553.0	553.0	1.110	1.008	1.008	.1237	.0763	.9925
6	30.09	27.48	27.48	27.14	3.51	.506	.351	50.84	48.3	555.5	552.0	554.0	1.109	1.013	1.013	.1457	.0942	.9600
7	29.99	27.64	27.64	27.10	3.50	.607	.417	49.76	50.5	555.6	553.5	554.5	1.107	1.020	1.020	.1751	.1190	1.015
8	29.99	19.91	19.91	20.0	3.54	.344	0	141.7	137.2	549.0	549.0	548.0	1.500	.9965	.9955	.0621	0	.9654
9	30.19	20.04	20.04	20.0	3.56	.398	.151	144.4	140.1	550.0	550.0	549.0	1.510	1.002	1.002	.0717	.0258	.9704
10	30.14	20.11	20.11	20.02	3.55	.438	.162	143.1	140.8	550.0	551.0	550.0	1.506	1.004	1.004	.0785	.0525	.9654
11	30.04	20.15	20.14	18.84	3.33	.434	.241	143.2	142.2	551.0	551.0	551.0	1.507	1.011	1.010	.0894	.0438	.9928
12	30.09	20.38	20.38	20.01	3.55	.394	.318	143.2	143.4	551.0	550.0	552.0	1.504	1.018	1.018	.1091	.0558	1.003
13	30.04	20.58	20.58	20.0	3.54	.635	.387	148.4	145.9	553.0	553.0	553.0	1.502	1.029	1.030	.1149	.0700	1.034
14	30.04	20.96	20.96	20.01	3.55	.730	.468	141.8	150.0	551.0	554.0	554.0	1.501	1.047	1.047	.1319	.0681	1.056
15	29.99	21.65	21.64	20.0	3.52	.889	.539	141.7	154.3	552.0	553.0	554.0	1.500	1.082	1.082	.1615	.1147	1.089
16	29.99	14.90	14.89	18.02	5.80	.312	0	193.6	181.3	549.0	550.0	550.0	1.988	.9997	.9990	.0659	0	.9678
17	30.14	15.09	15.10	15.06	5.63	.355	.107	194.6	194.8	550.0	552.0	552.0	2.001	1.002	1.003	.0601	.0164	1.00
18	30.04	15.11	15.10	14.99	5.66	.401	.168	194.4	193.4	550.0	553.0	553.0	2.004	1.008	1.007	.0687	.0365	.9845
19	30.14	15.25	15.25	15.03	5.64	.472	.258	194.9	196.4	551.0	553.0	553.0	2.005	1.015	1.015	.0810	.0403	1.018
20	30.14	15.58	15.57	15.03	5.68	.568	.324	194.9	201.9	551.0	554.0	553.0	2.006	1.035	1.035	.0874	.0568	1.036
21	30.14	15.80	15.78	15.09	5.64	.623	.381	196.3	201.9	551.0	555.0	554.0	2.007	1.052	1.051	.1070	.0653	1.054
22	30.14	16.42	16.42	15.01	5.66	.642	.312	196.8	211.9	550.0	555.0	554.0	2.015	1.094	1.094	.1445	.0977	1.077
23	30.14	17.34	17.27	14.94	5.66	1.077	.680	196.7	225.5	550.0	556.0	554.0	2.017	1.154	1.158	.1850	.1131	1.158
24	30.16	16.18	14.13	14.95	5.83	.721	.486	194.2	205.5	550.0	556.0	554.0	2.005	1.079	1.077	.1343	.0801	1.058
25	30.07	9.79	9.79	9.39	5.84	.252	0	236.3	238.9	548.0	544.5	539.5	3.010	.9780	.9600	.0396	0	1.011
26	30.02	10.09	10.10	10.02	5.62	.260	.150	235.6	240.5	548.0	544.0	544.0	2.996	1.007	1.008	.0446	.0282	1.090
27	30.12	10.19	10.20	10.03	5.62	.271	.197	235.8	240.3	549.0	548.0	546.0	3.005	1.016	1.017	.0465	.0537	1.016
28	30.02	10.41	10.41	10.02	5.63	.297	.266	235.6	241.0	549.0	547.5	547.5	2.996	1.039	1.039	.0506	.0458	1.005
29	30.12	10.73	10.73	10.01	5.83	.328	.329	235.8	244.8	549.0	548.0	548.0	3.009	1.072	1.072	.0588	.0585	1.035
30	29.92	11.59	11.59	10.02	5.83	.402	.454	234.5	248.1	549.0	549.0	548.5	2.885	1.137	1.137	.0690	.0744	1.068
31	30.07	12.15	12.15	10.01	5.86	.443	.397	235.9	256.0	550.0	549.5	550.0	3.005	1.214	1.214	.0696	.0901	1.085
32	30.02	13.35	13.40	10.01	5.92	.823	.550	235.8	263.0	551.0	550.0	549.5	2.999	1.337	1.337	.1097	.1117	1.128
33	40.58	9.53	9.52	10.0	7.78	.082	0	347.5	343.4	552.0	535.0	541.5	4.022	.985	.982	.0105	0	.9855
34	40.07	10.11	10.10	10.03	7.80	.108	.156	345.5	348.3	551.0	550.0	551.0	3.996	1.008	1.007	.0158	.0130	1.005
35	40.19	10.37	10.37	10.0	7.80	.135	.240	344.0	348.5	551.0	551.0	551.0	4.018	1.037	1.037	.0187	.0534	1.001
36	40.19	10.67	10.68	10.01	7.81	.156	.297	344.3	349.1	551.0	551.0	551.0	4.011	1.066	1.064	.0174	.0679	1.008
37	40.26	11.06	11.06	10.01	7.81	.196	.375	347.0	351.2	555.0	551.0	551.0	4.021	1.104	1.104	.0213	.0494	1.012
38	40.20	11.69	11.68	10.02	7.78	.212	.480	344.5	354.2	554.0	553.0	552.0	4.019	1.187	1.188	.0672	.0580	1.026
39	40.06	12.33	12.21	9.99	7.77	.236	.521	345.2	355.5	555.0	552.0	552.0	4.009	1.224	1.224	.0332	.0470	1.036
40	40.20	13.69	13.71	10.02	7.77	.396	.645	346.6	371.9	555.0	552.0	552.0	4.012	1.566	1.568	.0510	.0629	1.075
41	40.20	13.04	13.04	10.01	7.78	.327	.593	345.8	360.0	559.0	555.0	552.0	4.015	1.303	1.303	.0450	.0761	1.056
42	40.15	12.69	12.70	10.03	7.80	.297	.544	346.0	364.0	553.0	558.0	551.0	4.003	1.266	1.266	.0341	.0721	1.042
43	40.20	12.84	12.88	10.00	7.81	.259	.525	347.0	361.9	552.0	553.0	552.0	4.080	1.294	1.294	.0552	.0670	1.045
44	40.20	13.58	13.50	10.02	7.82	.347	.511	345.8	389.7	551.0	554.0	553.0	4.018	1.325	1.327	.0445	.0782	1.087
45	55.30	9.45	9.44	9.16	10.76	0	.179	519.6	515.8	553.0	553.0	553.0	5.087	1.029	1.051	0	.0164	.9925
46	55.56	10.37	10.29	9.16	10.77	.082	.275	523.3	523.3	551.0	552.0	551.0	5.081	1.119	1.121	.0090	.0255	1.002
47	55.25	10.67	10.68	9.15	10.76	.032	.315	516.8	521.9	551.0	562.0	561.0	5.058	1.167	1.167	.0294	.0290	1.006
48	55.30	11.42	11.45	9.17	10.77	.082	.381	519.5	527.8	551.0	552.0	551.0	5.031	1.243	1.243	.0048	.0565	1.019
49	55.50	12.40	12.42	9.15	10.74	.081	.476	523.7	534.8	550.0	552.0	551.0	5.044	1.351	1.351	.0075	.0442	1.039
50	55.15	13.02	13.02	9.17	10.75	.101	.515	517.5	534.1	550.0	552.0	551.0	5.014	1.401	1.396	.0094	.0471	1.050
51	55.30	13.95	13.91	9.17	10.75	.154	.601	519.5	545.6	550.0	550.0	551.0	5.031	1.514	1.517	.0143	.0580	1.065
52	55.30	14.70	14.74	9.17	10.72	.206	.667	519.7	552.4	550.0	550.0	552.0	5.051	1.603	1.607	.0085	.0485	1.065
53	55.18	9.54	9.53	9.31	10.76	0	.288	519.0	563.0	544.0	546.0	541.0	5.497	1.514	1.616	0	.0267	1.027
54	55.18	10.28	10.22	8.80	10.75	.082	.348	548.3	567.1	548.0	548.0	545.0	5.343	1.762	1.762	.0081	.0321	1.033
55	55.18	10.87	10.66	8.80	10.74	.038	.394	548.5	575.1	548.0	546.0	545.0	5.314	1.874	1.871	.0038	.0387	1.044
56	55.23	11.71	11.70	8.81	10.77	.052	.461	548.7	578.8	548.0	546.0	546.0	5.505	2.015	2.014	.0090	.0496	1.053
57	55.15	12.47	12.43	8.80	10.72	.096	.528	548.4	584.4	548.0	546.0	546.0	5.505	2.164	2.160	.0081	.0487	1.068
58	55.15	12.68	12.81	8.81	10.71	.080	.560	548.0	585.2	546.0	546.0	546.0	5.497	2.177	2.170	.0080	.0494	1.068
59	55.15	13.60	13.61	8.80	10.72	.146	.603	548.6	591.6	547.0	546.0	546.0	5.522	2.345	2.347	.0135	.0565	1.078
60	55.22	14.50	14.49	8.81	10.71	.197	.647	548.5	596.7	548.0	547.0	547.0	5.506	2.496	2.498	.0184	.0624	1.080
61	55.35	9.39	9.37	8.98	10.76	0	.274	540.8	543.9	547.0	548.0	547.0	6.077	1.371	1.564	0	.0685	1.015
62	55.31	10.31	10.27	8.88	10.69	.035	.342	539.3	553.2	547.0	547.0	547.0	6.048	1.505	1.499	.0025	.0380	1.028
63	55.28	10.66	10.44	8.88	10.73	.056	.387	540.3	556.1	547.0	547.0	547.0	6.070	1.564	1.562	.0035	.0561	1.033
64	55.28	11.58	11.53	8.88	10.76	.087	.443	540.4	563.1	547.0	547.0	547.0	6.084	1.685	1.684	.0085	.0412	1.042
65	55.15	12.67	12.68	8.88	10.71	.099	.529	539.2	571.6	547.0	547.0	547.0	6.055	1.863	1.861	.0092	.0464	1.060
66	54.96	15.44	15.43	8.68	10.68	.134	.580	557.6	575.8	546.0	548.0	547.0	6.066	1.961	1.961	.0119	.0561	1.070
67	55.06	14.12	14.12	8.68	10.89	.192	.621	556.3	582.0	546.0	547.0	547.0	6.028	2.102	2.102	.0180	.0619	1.083

a Values obtained from nozzle calibration.

Secondary air

Primary air

Pivot point

Flexible connections

Tertiary air

Exhaust chamber

Flexiable hose

Outer shroud

p_o

P_s P_p P_t

T_s T_p T_t

Counter-weight

Thrust cell

Primary nozzle

Inner shroud

NACA
CD-2817

Figure 1. - Ejector-research facility.

Nozzle position	D_p (in.)	D_s/D_p	S_s/D_p	D_t/D_p	S_t/D_p	D_t/D_s	S_t/D_s
Open	4.79	1.18	0.59	1.32	0.75	1.12	0.635
Closed	3.49	1.62	.86	1.80	1.07	1.12	.663

Figure 2. - Ejector notation and description of ejector models.

(a) Primary-nozzle position, closed.

Figure 3. - Double-shroud ejector performance. Zero cooling-air flow.

(b) Primary-nozzle position, open.

Figure 3. – Concluded.   Double-shroud ejector performance.   Zero cooling-air flow.

(a) Primary-nozzle position, closed.

(b) Primary-nozzle position, open.

Figure 4. - Effect of primary pressure ratio on gross thrust ratio. Zero cooling-air flow.

(a) Primary-nozzle position, closed.

Figure 5. - Effect of primary pressure ratio on backflow.

$$\frac{W_s}{W_p}\sqrt{\frac{T_s}{T_p}} = -\frac{W_t}{W_p}\sqrt{\frac{T_t}{T_p}}$$

Weight-flow ratio

Normal secondary flow

Secondary backflow

Tertiary backflow

Normal tertiary flow

Primary pressure ratio, P_p/P_0

(b) Primary-nozzle position, open.

Figure 5. – Concluded. Effect of primary pressure ratio on backflow.

Figure 6. - Effect of tertiary pressure ratio on secondary and
  tertiary weight-flow ratios with primary nozzle in closed
  position. Primary pressure ratio, P_p/p_0, 2.99; secondary

pressure ratio, P_s/p_0, 1.302.

Figure 7. - Effect of secondary pressure ratio on secondary and
    tertiary weight-flow ratios with primary nozzle in closed
    position.   Primary pressure ratio, P_p/p_0, 2.99; tertiary
    pressure ratio, P_t/p_0, 1.304.

Figure 8. - Effect of tertiary pressure ratio on secondary and tertiary weight-flow ratios with primary nozzle in open position. Primary pressure ratio, P_p/p_0, 3.0; secondary pressure ratio, P_s/p_0, 1.304.


Figure 9. - Effect of secondary pressure ratio on secondary and tertiary weight-flow ratios with primary nozzle in open position. Primary pressure ratio, P_p/p_0, 3.015; secondary pressure ratio, P_s/p_0, 1.303.

(a) Effect of secondary and tertiary pressure ratios on secondary weight-flow ratio.

Figure 10. - Double-shroud ejector pumping characteristics with primary nozzle in closed position.

(b) Effect of secondary and tertiary pressure ratios on tertiary
weight-flow ratio.

Figure 10. - Concluded. Double-shroud ejector pumping characteristics with primary
nozzle in closed position.

(a) Effect of secondary and tertiary pressure ratios on secondary weight-flow ratio.

Figure 11. - Ejector pumping characteristics with primary nozzle in open position.

(b) Effect of secondary and tertiary pressure ratios on tertiary weight-flow ratio.

Figure 11. - Concluded. Ejector pumping characteristics with primary nozzle in open position.

(a) Primary-nozzle position, closed.

Figure 12. - Double-shroud ejector thrust characteristics.

(b) Primary-nozzle position, open.

Figure 12. - Concluded. Double-shroud ejector thrust characteristics.